

What is claimed is:

1. A cargo handling vehicle comprising:

a cargo carrier for carrying a cargo thereon;

a lift unit for raising and/or lowering the cargo carrier;

a vehicle main body for moving the lift unit forward and backward;

a lift height detecting section for detecting the vertical position of the cargo carrier;

a traveling distance measuring section for measuring a forward distance moved by the vehicle main body;

a measurement start indication section for starting the measurement of the traveling distance measuring section when the lift unit moves in the forward direction after the height of the cargo carrier is not less than a predetermined height and the lift unit stops during a predetermined period; and

a movement control section for prohibiting the lowering movement of the cargo carrier until a rearward distance moved by the vehicle main body is not more than a predetermined value after the measurement start indication section starts the measurement.

2. The cargo handling vehicle as claimed in claim 1, wherein the traveling distance measuring section is an up-down counter for up-counting the forward distance moved by the lift unit, and down-counting the rearward distance moved thereby;







8. A cargo handling vehicle comprising:  
 a cargo carrier for carrying a cargo thereon;  
 a lift unit for raising and/or lowering the cargo carrier;  
 a vehicle main body for moving the lift unit forward and backward;

a cargo detection section for detecting the cargo on the cargo carrier;

a lift height detecting section for detecting the vertical position of the cargo carrier;

a traveling distance measuring section for measuring a forward distance moved by the vehicle main body;

a measurement start indication section for starting the measurement of the traveling distance measuring section when the detection results of the cargo detection section is changed after the lift height detecting section detects that the height of the cargo carrier is not less than a predetermined height; and

a movement control section for prohibiting the lowering movement of the cargo carrier until the measured value of the traveling distance measuring section is not more than a predetermined value after the measurement start indication section starts the measurement.

9. The cargo handling vehicle as claimed in claim 8, wherein the movement control section allows lowering the cargo

carrier by the lift unit within a predetermined range, and prohibits lowering the cargo carrier below the predetermined range.

10. The cargo handling vehicle as claimed in claim 8, wherein the movement control section forcibly stops lowering the cargo carrier.

COPPER-100	
Year	Value
1990	100
1991	100
1992	100
1993	100
1994	100
1995	100
1996	100
1997	100
1998	100
1999	100
2000	100
2001	100
2002	100
2003	100
2004	100
2005	100
2006	100
2007	100
2008	100
2009	100
2010	100
2011	100
2012	100
2013	100
2014	100
2015	100
2016	100
2017	100
2018	100
2019	100
2020	100
2021	100
2022	100
2023	100
2024	100
2025	100
2026	100
2027	100
2028	100
2029	100
2030	100
2031	100
2032	100
2033	100
2034	100
2035	100
2036	100
2037	100
2038	100
2039	100
2040	100
2041	100
2042	100
2043	100
2044	100
2045	100
2046	100
2047	100
2048	100
2049	100
2050	100
2051	100
2052	100
2053	100
2054	100
2055	100
2056	100
2057	100
2058	100
2059	100
2060	100
2061	100
2062	100
2063	100
2064	100
2065	100
2066	100
2067	100
2068	100
2069	100
2070	100
2071	100
2072	100
2073	100
2074	100
2075	100
2076	100
2077	100
2078	100
2079	100
2080	100
2081	100
2082	100
2083	100
2084	100
2085	100
2086	100
2087	100
2088	100
2089	100
2090	100
2091	100
2092	100
2093	100
2094	100
2095	100
2096	100
2097	100
2098	100
2099	100
2100	100

a lift height detecting section for detecting the vertical position of the cargo carrier;

a traveling distance measuring section for measuring a forward distance moved by the vehicle main body;

a measurement start indication section for starting the measurement of the traveling distance measuring section when the lift unit moves in the forward direction not less than a predetermined distance after the height of the cargo carrier is not less than a predetermined height, and then the cargo carrier moves up and down within a predetermined range, and then the lift unit starts to move backward; and

a movement control section for prohibiting the lowering movement of the cargo carrier until the measured value of the traveling distance measuring section is not more than a predetermined value after the measurement start indication section starts the measurement.

12. The cargo handling vehicle as claimed in claim 11, wherein the movement control section allows lowering the cargo carrier by the lift unit within the predetermined range, and





14. A cargo handling vehicle comprising:

a cargo carrier for carrying a cargo thereon;

a lift unit for raising and/or lowering the cargo carrier;

a vehicle main body for moving the lift unit forward and backward;

a cargo detection section for detecting the cargo on the cargo carrier;

a traveling distance measuring section for measuring a rearward distance of the lift unit moved by the vehicle main body;

a measurement start indication switch for starting the measurement of the traveling distance measuring section; and

a rearward movement control section for stopping the rearward movement of the vehicle main body when the measured value of the traveling distance measuring section reaches a predetermined value.

15. The cargo handling vehicle as claimed in claim 14, further comprising a movement control section for prohibiting lowering the cargo carrier by the lift unit until the measured value of the traveling distance measuring section reaches a predetermined value.

16. The cargo handling vehicle as claimed in claim 14,  
wherein the movement control section forcibly stops lowering

the cargo carrier.

T. 044T. 030" 03664360





22. The cargo handling vehicle as claimed in claim 20, wherein the movement control section forcibly stops lowering the cargo carrier.

09499-06404  
09499-06404

23. A cargo handling vehicle comprising:  
a cargo carrier for carrying a cargo thereon;  
a lift unit for raising and/or lowering the cargo carrier;  
a vehicle main body for moving the lift unit forward and backward;

a cargo detection section for detecting the cargo on the cargo carrier;

a traveling distance measuring section for measuring a rearward distance of the lift unit moved by the vehicle main body;

a measurement start indication switch for starting the measurement of the traveling distance measuring section;

a rearward movement start section for automatically starting the lift unit to move backward by operating the measurement start indication switch; and

an alarm section for put out an alarm when the measured value of the traveling distance measuring section reaches a predetermined value.

24. The cargo handling vehicle as claimed in claim 23, further comprising a movement control section for prohibiting lowering the cargo carrier by the lift unit until the measured value of the traveling distance measuring section reaches a predetermined value.

25. The cargo handling vehicle as claimed in claim 24, wherein the movement control section forcibly stops lowering the cargo carrier.

09079995 064404  
T04T90" 55552050

26. A cargo handling vehicle comprising:  
 a cargo carrier for carrying a cargo thereon;  
 a lift unit for raising and/or lowering the cargo carrier;  
 a vehicle main body for moving the lift unit forward and backward;

a traveling distance measuring section for measuring a rearward distance of the lift unit moved by the vehicle main body;

a measurement start indication switch for starting the measurement of the traveling distance measuring section;

a automatic lowering section for automatically lowering the cargo carrier by the lift unit when the measured value of the traveling distance measuring section reaches a predetermined value.

27. The cargo handling vehicle as claimed in claim 26, further comprising an operation lever for operating the lift unit to lift the cargo carrier up and down,

wherein the measurement start indication switch is provided on a knob of the operation lever.

28. The cargo handling vehicle as claimed in claim 26, wherein the vehicle main body is a forklift truck, and the cargo carrier is a fork supporting the cargo mounted on a pallet;  
 the lift unit comprises a mast for supporting the fork





30. A reach forklift truck comprising:

a mast;

a fork for carrying a cargo thereon;

a lift unit for raising and/or lowering the fork along with the mast;

a straddle arm;

a reach device moving the lift unit in the forward and rearward direction along with the straddle arm;

a vehicle main body having a tire for running the reach forklift truck;

a lift height detecting section for detecting the vertical position of the cargo carrier;

a lift unit traveling distance measuring section for measuring a forward distance of the lift unit moved by the reach device;

a measurement start indication switch for starting the measurement of the lift unit traveling distance measuring section; and

a movement control section for prohibiting the lowering movement of the cargo carrier until the measured value of the lift unit traveling distance measuring section is equal to or below a predetermined value when the height of the fork measured by the lift height detecting section is equal to or above a predetermined height.

31. The reach forklift truck as claimed in claim 30, wherein the movement control section allows lowering the cargo carrier by the lift unit within a predetermined range, and prohibits lowering the cargo carrier below the predetermined range.

32. A reach forklift truck comprising:

a mast;

a fork for carrying a cargo thereon;

a lift unit for raising and/or lowering the fork along  
with the mast;

a straddle arm;

a reach device moving the lift unit in the forward and rearward direction along with the straddle arm;

a vehicle main body having a tire for running the reach  
forklift truck;

a lift unit traveling distance measuring section for measuring a forward distance of the lift unit moved by the reach device;

a vehicle body traveling distance measuring section for measuring a forward distance of the vehicle main body moved;

a measurement start indication switch for starting the measurement of the lift unit traveling distance measuring section and the vehicle body traveling distance measuring section;

an adder for adding the measured distances of the lift unit traveling distance measuring section and the vehicle body traveling distance measuring section to output an added value; and

a movement control section for prohibiting the lowering movement of the cargo carrier until the added value of the lift

unit traveling distance measuring section and the vehicle body traveling distance measuring section is equal to or below a predetermined value.

33. The reach forklift truck as claimed in claim 32, further comprising:

a lowering start indication section for controlling the lift unit to automatically lower the fork when the added value thereof is not more than the predetermined value; and

a lowering reservation switch for operating the lowering start indication section.

34. The reach forklift truck as claimed in claim 32, further comprising a vehicle automatic stop section for automatically stopping the rearward movement of the vehicle main body when the added value thereof is not more than the predetermined value.

35. A reach forklift truck comprising:

a mast;

a fork for carrying a cargo thereon;

a lift unit for raising and/or lowering the fork along with the mast;

a straddle arm;

a reach device moving the lift unit in the forward and rearward direction along with the straddle arm;

a vehicle main body having a tire for running the reach forklift truck;

a lift height detecting section for detecting the vertical position of the cargo carrier;

a lift unit traveling distance measuring section for measuring a forward distance of the lift unit moved by the reach device;

a vehicle body traveling distance measuring section for measuring a forward distance of the vehicle main body moved;

an adder for adding the measured distances of the lift unit traveling distance measuring section and the vehicle body traveling distance measuring section to output an added value;

a measurement start indication section for starting the measurement of the lift unit traveling distance measuring section and the vehicle body traveling distance measuring section when the lift unit starts to move backward after the reach device moves the lift unit forward under the condition

that the height of the fork measured by the lift height detecting section is equal to or above the a predetermined height; and

a movement control section for prohibiting the lowering movement of the cargo carrier until the added value of the lift unit traveling distance measuring section and the vehicle body traveling distance measuring section is equal to or below a predetermined value.

36. The reach forklift truck as claimed in claim 35, further comprising:

a lowering start indication section for controlling the lift unit to automatically lower the fork when the added value thereof is not more than the predetermined value; and

a lowering reservation switch for operating the lowering start indication section.

37. The reach forklift truck as claimed in claim 35, further comprising a vehicle automatic stop section for automatically stopping the rearward movement of the vehicle main body when the added value thereof is not more than the predetermined value.

